

BEACON HILL™ SMOOTH 60mm

ENDURACOLOR™



ALMOND GROVE FUSION
NOT AVAILABLE IN SLAB



GRANITE FUSION



OPAL BLEND

34
SRI



TUSCANY

44
SRI



DARK BROWN
SMALL RECTANGLE BUNDLE ONLY



MIDNIGHT CHARCOAL
SMALL RECTANGLE BUNDLE ONLY



OPAL BLEND
SMALL RECTANGLE BUNDLE ONLY



SMALL RECTANGLE BUNDLE
7 1/2 x 15 x 2 3/8"
190 x 380 x 60mm

34
SRI

PRODUCT ATTRIBUTES

Visual Appearance	Beacon Hill Smooth offers a smooth surface texture for a sleek, modern look with a contemporary colour palette.
Finish	Smooth with Enduracolor finish.

RECOMMENDED SAND



Gator G2 MAXX Sand

- | Setting time - 15 mins
- | Sets above 32° F/ 0° C
- | Can be applied if rain is expected (min. 1 hr)
- | Dust free and haze free
- | Requires only one watering
- | Four colours: Beige, Grey, Black and Ivory

Coverage:

Colour	Narrow Joints	Wide Joints
Beige, Grey, Ivory 50lb. bag	65-85 sqft	22-42 sqft
Black 50lb. bag	58-76 sqft	20-38 sqft

RECOMMENDED SEALER




Gator Natural Look Sealer

- | Water-based
- | Zero gloss finish
- | Multi purpose
- | Rain safe after 24 hours

Coverage:

Size	Area
3.78 L / 1 U.S. gal.	175 sqft
18.9 L. / 5.28 U.S. gal.	875 sqft

PRODUCT SPECIFICATIONS




LARGE RECTANGLE
15 x 22 7/16 x 2 3/8"
380 x 570 x 60mm



SQUARE
15 x 15 x 2 3/8"
380 x 380 x 60mm



SMALL RECTANGLE
7 1/2 x 15 x 2 3/8"
190 x 380 x 60mm



SLAB
22 7/16 x 37 3/8 x 2 3/8"
570 x 950 x 60mm
See Slabs section page 84 for more details.


3 UNIT RANDOM BUNDLE

EDGE DETAILS





ROUNDED EDGE

BUNDLE CONFIGURATION



LAYING PATTERNS



BHS A
14% Small Rectangle, 28% Square, 28% Large Rectangle, 28% XL Rectangle

BHS B
14% Small Rectangle, 28% Square, 28% Large Rectangle, 28% XL Rectangle

TECHNICAL INFORMATION

ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units

Conforms to:

- C140 for Absorption 4% avg - 5% max
- Compressive Strength > 8,000 PSI avg.
- C1645 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy +/- 3mm

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

TECHNICAL ADVANTAGES

ENDURACOLOR

Refined surface and long-lasting colour

PEDESTRIAN FRIENDLY

Not recommended for vehicular

SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS

Product	Solar Reflectance	SRI
Opal Blend	0.32	34
Tuscany	0.39	44

LEED INFORMATION

Materials & Resources: LEED V4:

- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • 1 point
- Sourcing of Raw Materials - Leadership Extraction Practices • 1 point
- Material Ingredient Reporting - Material Ingredient Reporting • 1 point
- Material Ingredient Reporting - Material Ingredient Optimization • 1 point
- Environmental Product Declaration • 1 point

PRODUCT DATA (NEW FORMAT)

Stones & Bundling	Unit Thickness	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per		Lbs Per		
		Bundle	Layer	Section	Stone	Layers	Section	SqFt	Layer	Bundle	Unit	Layer	Bundle	SqFt	Bundle	Layer	Section	Bundle
Pickering Manufacturing / Beacon Hill Flagstone 6cm Almond Grove Fusion stocked in Ayr																		
Random Bundle		104.92	11.65			9	-	-	-	-	0.99	9.35	84.15	0.76	72	319.93	-	2,879.4
Large Rectangle	2 3/8" (60mm)	-	4.66	-	2.331	-	-	-	-	-	1.87	3.74	33.66	0.48	18		-	-
Small Rectangle	2 3/8" (60mm)	-	4.66	-	0.777	-	-	-	-	-	0.63	1.87	16.83	1.43	27		-	-
Square	2 3/8" (60mm)	-	2.33	-	1.554	-	-	-	-	-	1.25	3.74	33.66	0.72	27		-	-
Small Rectangle (Smooth only)	2 3/8" (60mm)	104.92	11.657		0.777	9	-	1.25	-	84.38	0.63	-	168.75	1.43	135	319.93		2,879.4
Slab	2 3/8" (60mm)	69.94	11.66		5.83	6		1.87		22.44	3.12		37.38	0.17	12	319.80		1,918.80

Notes: Sold in full bundles only on a refundable skid. Beacon Hill 60mm is not intended for vehicular applications. All measurements are nominal. **Important: A urethane rubber paver mat must be used to prevent scuffing.** Contact your Unilock Territory Manager or call 1-800-UNILOCK for further information. *For custom options, please contact your Unilock Territory Manager.

APPLICATIONS



Pedestrian



Wall pairing suggestion- U-CARA - matching colour and finish



Roof Deck